



**Retractable Mounting Arm** allows rigid mounting of instruments away from tower to minimize effect of the tower structure on measurements. Tele-scopic design retracts for easy installation and service of sensor. Constructed of galvanized steel square tubing, the mounting arm is supplied with universal mounting brackets that bolt to tower legs. 1" IPS mounting post fits YOUNG sensors.

## Specifications

### Model 16106:

Length: 6 ft  
 Tubing size: 1.5 in  
 Max tower width: 20 in  
 Tower leg dia. (max.): 2 in  
 Weight (approx.) : 20 lb

### Model 16208:

Length: 8 ft  
 Tubing size: 2.0 in  
 Max tower width: 30 in  
 Tower leg dia. (max.): 2.5 in  
 Weight (approx.): 40 lb

*Specifications subject to change without notice.*

## Ordering Information

	MODEL
RETRACTABLE MOUNTING ARM – 6 ft. (1.8m)..... For small towers to 20" side.	16106A
RETRACTABLE MOUNTING ARM – 8 ft. (2.4m)..... For towers to 30" side.	16208A



**R. M. YOUNG COMPANY**  
 2801 Aero Park Drive  
 Traverse City, Michigan 49686 USA  
 TEL: (231) 946-3980 FAX: (231) 946-4772  
 E-mail: met.sales@youngusa.com  
 Web Site: www.youngusa.com