NEW!

Precipitation



YOUNG

Model TR-525-W2-S
200 mm Rainfall Tipping Bucket

YOUNG Model TR-525-W2-S 200 mm Rainfall Tipping Bucket



The TR-525-W2-S Rainfall Sensor with a WMO standard 200mm diameter funnel is a remote tipping bucket style rain gauge that measures liquid precipitation. It utilizes a unique siphoning mechanism that allows an extended range of accuracy. This system allows control of the "flow rate" of accumulated precipitation. This metering geometry assures higher levels in both accuracy and repeatability during periods of extremely heavy rainfall. The Rain Gauge is a freestanding receptacle for measuring precipitation. The TR-525-W2-S was specifically designed to meet the National Weather Service & World Meteorological Organization requirements for rainfall measurement.

Installation consists of attaching the three sensor support legs to a firm platform (such as our MB-525 Mounting Base). Pole mounting on the mast of a weather station is available by securing to the included side bracket.

Maintenance consists of routine cleaning of debris from the filter screen, and occasional calibration verification with our FC-500 Field Calibration Kit.

Key Features

- Unique siphoning technique allows for wide accuracy
- Meets WMO requirements for a 200 mm collector
- Interfaces with virtually all data acquisition systems
- Knife-edge collector optimizes rainfall catch
- Exceptional splash-out protection improves accuracy in high winds
- Easy installation and maintenance
- Rugged aluminum exterior
- Anodized and powder coated aluminum collector for weather resistance
- Integrated bubble level

Specifications

Resolution:	0.1 mm, 0.2 mm, 0.5 mm 1.0 mm (additional fee), 0.01"
Accuracy:	0-10 in (254 mm per hour), ±2% 10-20 in (508 mm per hour), ±3%
Siphon Starting Threshold:	<0.01" (<0.254 mm)
Range:	27" (700 mm) per hour
Collector Diameter:	200 mm with knife-edge
Funnel Depth:	6.4" (163 mm)
Splash Out Protection:	>2" (50 mm)
Operating Temp:	32-158° F (0-70° C)
Storage Temp:	-40-185° F (-40-85° C)
Humidity Limits:	0-100%
Weight:	1.8 lbs
Height:	11.125" (283 mm)
Cable:	10', 24 gauge, 2 conductor
Switch:	Momentary potted reed switch
Switch Rating:	30 VDC @ 2 A, 115 VAC @ 1 A
Switch Closure Time:	135 ms
Bounce Settling Time:	0.75 ms
Pivot:	Ground bronze pivots with hardened stainless steel shaft
Bucket:	Black PP injection molded
Level:	Integral bubble level
Warranty:	3 years

Ordering Information

Model #: TR-525-W2-S
Description: Rain Gauge, 200 mm collector (Please specify calibration)

Optional Parts / Accessories:

MB-525	Pole Mounting Base
FC-500	Field Calibration Kit
BB-525	Bird Repellent
HT-525	Heater, 120 VAC

R.M. Young Company
2801 Aero Park Drive
Traverse City, Michigan 49686 USA
Tel: (231) 946-3980 Fax: (231) 946-4772
Email: met.sales@youngusa.com
Web: www.youngusa.com

CE

Complies with applicable CE directives.
Specifications subject to change without notice.

Copyright © 2026 R.M. Young Company, Printed in U.S.A. 2026