NEW!

Precipitation



YOUNG

Model TR-525I
6” Rainfall Tipping Bucket

YOUNG Model TR-525I 6” Rainfall Tipping Bucket



The TR-525I Rainfall Sensor with 6” diameter funnel is a remote tipping bucket style rain gauge that measures liquid precipitation. The Rain Gauge is a freestanding receptacle for measuring precipitation. Through an opening at the top of the device, rain is collected and then funneled to a mechanical device, called a tipping bucket. As water is collected, the tipping bucket fills to the point that it tips over, causing a momentary closure of a switch to incrementally measure rainfall accumulation. This action empties the bucket in preparation for additional measurement. Water discharged by the tipping bucket passes out of the rain gauge with no need for emptying. The TR-525I is a rugged and reliable rain gauge that delivers high accuracy at a low cost.

Installation consists of attaching the three sensor support legs to a firm platform (such as our MB-525 Mounting Base). Pole mounting on the mast of a weather station is available by securing to the included side bracket.

Maintenance consists of routine cleaning of debris from the filter screen, and occasional calibration verification with our FC-500 Field Calibration Kit.

Key Features

- Interfaces with virtually all data acquisition systems
- Knife-edge collector optimizes rainfall catch
- Exceptional splash-out protection improves accuracy in high winds
- Easy installation and maintenance
- Over 30 years in production
- Lightweight aluminum exterior
- Powder coated aluminum collector for weather resistance and better water shedding
- Integrated bubble level
- 2 thumb screws to hold collector secure

Specifications

Resolution:	0.01” English, 0.2 mm (optional)
Accuracy:	0-2 in. (50 mm) per hour, ±1%
Range:	27” (700 mm) per hour
Collector Diameter:	6.06” (154 mm) with knife-edge
Funnel Depth:	>6.5” (165 mm)
Splash Out Protection:	>2” (50 mm)
Operating Temp:	32-158° F (0-70° C)
Storage Temp:	-40-185° F (-40-85° C)
Humidity Limits:	0-100%
Weight:	1.6 lbs
Height:	10.25” (260 mm)
Cable:	10’, 24 gauge, 2 conductor
Switch:	Momentary potted reed switch
Switch Rating:	30 VDC @ 2 A, 115 VAC @ 1 A
Switch Closure Time:	135 ms
Bounce Settling Time:	0.75 ms
Pivot:	Ground bronze pivots with hardened stainless steel shaft
Bucket:	Black PP injection molded
Level:	Integral bubble level
Warranty:	3 years

Ordering Information

Model #: TR-525I
Description: Rain Gauge, 6.06” collector
(Please specify for calibration of 0.2 mm/tip)

Optional Parts / Accessories:

HOBO	Pendant Datalogger
MB-525	Pole Mounting Base
FC-500	Field Calibration Kit
BB-525	Bird Repellent
HT-525	Heater, 120 VAC

R.M. Young Company
2801 Aero Park Drive
Traverse City, Michigan 49686 USA
Tel: (231) 946-3980 Fax: (231) 946-4772
Email: met.sales@youngusa.com
Web: www.youngusa.com

CE

Complies with applicable CE directives.
Specifications subject to change without notice.

Copyright © 2026 R.M. Young Company, Printed in U.S.A. 2026